briteline™

MultiGRIP

briteline.com

Briteline® MultiGRIP is a 14mil non-slip textured PVC film that is reinforced with fabric on the adhesive side to add extra durability and strength. MultiGRIP can be cut into any shape and can be applied to nearly any surface and removed with little to no residue left behind. MultiGRIP eliminates the need for a UL approved anti-slip laminate for it is ASTM-D2047 certified non-slip film. This film is a perfect solution for tradeshows, POS and retail, universities, outdoor events and anywhere that calls for a graphic that is easy to print, install and remove.

Applications

MultiGRIP is designed for wall and floor graphics, indoor use or short term outdoor use. Surfaces recommended include, but are not limited to; carpet, tile, metal, properly painted surfaces, wood and PVC floors, untreated stone, smooth concrete, asphalt, brick and ceramic tile. (Please see durability expected permanence).

Ink Compatibility

Optimized for solvent, eco-solvent, latex and UV inks

Application Instructions

Remove dirt and debris from the surface the graphic will be applied to; recommended application surface temperature is 50°F. Use a soft rubber roller or squeegee on the surface of the graphic removing any bubbles and making sure the adhesive is making full contact with the surface.

Thickness

Applied Graphic	14 mil
Substrate	12 mil
Reinforced Adhesive	2 mil
Release Liner	5 mil

Certifications

E-84 Class A fire rated
ASTM-D2047 non-slip passed

Durability

Interior Floors	4+ months
Interior Walls	3+ years
Exterior Surfaces (pedestrian traffic ONLY, concrete, brick & asphalt)	3 months
Exterior Walls (smooth concrete, brick or stucco)	3 months

Removal Instruction

Peel back a corner at 45° angle. With even continuous motion, pull back graphic at a 180° angle. If one pulls back at a 90° angle, the chances of adhesive being left behind are more likely.

Product Series

BL-MG4825	48″ x 25′
BL-MG48100	48″ x 100′

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions or sale, including disclaimer of warranties and limitation of liability.