JESSUP CatWalk®

Slip-Resistant Graphics for Wet Indoor Environments

- Ideal for indoor floor graphics
- Tolerates water in showers, and around swimming pools
- Extremely secure with its slip-resistant surface
- Resists common cleaning chemicals
- No lamination required
- Lasts up to 3+ months

Built for wet environments

- Showers, bathtubs
- Indoor pool areas
- Locker rooms
- Wet commercial environments
- Temporary floor campaigns



Slip-resistant and chemical-resistant surface

Holds up under foot traffic

Slip-resistant surface for pedestrian safety



No overlaminate needed

Printable with UV inkjet, latex, solvent, eco-solvent.

Easy to clean surface

Easy to apply and remove with minimal residue

JESSUP® Adhesive Coated Films

jessupmfg.com

JESSUP CatWalk®





Sizes:
Floor01-W-3 (27" x 10')
Floor01-W-10 (54" x 33')
Floor01-W-100 (54" x 100')

Duration:
Up to 3 months indoors

Certifications:
- UL 410
- R10 Rated (DIN 51130)
- ASTM D-2047 Tested

CatWalk® applies to:
- Commercial carpet
- Tiles
- Marble
- Concrete
- Linoleum
- Porcelain
- Vinyl

PHYSICAL PROPERTIES	TEST METHODS	AVERAGE RESULTS
Thickness	PSTC - 133 - Substrate - Pressure Sensitive adhesive - Release Liner	 0.018 inch (0.457 mm) 0.002 inch (0.051 mm) 0.007 inch (0.178 mm)
Peel Adhesion to:	PSTC – 101	
- Stainless Steel	15 minute dwell 24 hour dwell	55 oz/in (66 N/100 mm) 75 oz/in (82 N/100 mm)
- Powder coated surfaces*	15 minute dwell 24 hour dwell	40 oz/in (44 N/100 mm) 55 oz/in (60 N/100 mm)
- Polyethylene	15 minute dwell 24 hour dwell	20 oz/in (22 N/100 mm) 25 oz/in (27 N/100 mm)
Shear Adhesion to:	PSTC – 107	
- Stainless Steel	1/2" x 1/2" x 1000g	<5 hours
Tack	PSTC - 6 Rolling Ball Tack	<5 inches

Note: *While the data contained herein is believed to be reliable averages of the properties, the data should not be used for specification purposes. Color and lot variances of carpet and coated surfaces including paints, powder coatings, lacquers, stains, and other treatments may vary the performance and should be evaluated for the compatibility of the tape to the specific surface.*

Print n'Go Media™ **No laminate required**

JESSUP® Adhesive Coated Films

Jessup Manufacturing Company

©Jessup MKT-JMC-CatWalk